

SOUNDPROOFED GEN SETS WITH IVECO ENGINE



1500 RPM	400/230 V 50 Hz	Type II-060	60/48 Kva/KW (PRP)	66/52,5 Kva/KW (LTP)
-----------------	------------------------	--------------------	---------------------------	-----------------------------

Engine: NEF 45 SM1
Alternator: ECO32-2L/4

Scope of Supply:

The engine and the alternator are mounted together forming a rigid monoblock, the shafts are connected by a flexible disc connection. The monoblock is mounted via silent blocks inside a steel plate soundproofed canopy including a built in fuel tank. The canopy is painted with powder paint and covered with noise insulator material. Starting is electric and it includes a battery. The genset monitoring system consist of a control module.

GEN SET POWER

Voltage	Hz	Phase	Cos Ø	PRP* Kva/KW	LTP** Kva/KW	Amp.
415/240	50	3	0,8	60/48	66/52,8	91,9
400/230	50	3	0,8	60/48	66/52,8	95,4
380/220	50	3	0,8	60/48	66/52,8	100,4
240/139	50	3	0,8	60/48	66/52,8	159
230/133	50	3	0,8	60/48	66/52,8	165,9
220/127	50	3	0,8	60/48	66/52,8	173,4

PRP* Kva/KW:

Available electrical power (at a variable load) with a medium of 80% of the indicated maximum power. A 10% overload capability is available

LTP** Kva/KW:

Available electrical load (at a variable load) during a maximum of 500 hours per year. No overload capability is available.

Control Cubicle Alternatives

Manual/Remote Control Cubicle:: STANDARD MCP SAM 712 / OPTIONAL MCP DSE 710
 Automatic Control Cubicle: STANDARD ACP DSE 720 / OPTIONAL ACP DSE 5320

Options::

Please see the price list