



Brand New 4 kVa 230v Diesel Engined Generator



Yanmar L48AEDG Air Cooled, 3000rpm, 12v Electric Start/Stop Diesel Engine, c/w Low Oil Level and High Engine Temperature Shutdown Protection
Meccalte SW16, brushless, 2 pole alternator, 230v single phase output. 50Hz.

Unit is housed in a powder coated mild steel acoustic enclosure 65dBa at 7m, access is possible whilst the generator is in situ as both side panels and the top panel are secured by heavy duty over centre catches, meaning that service and general maintenance can be carried out without removing the generator from the enclosure, the unit is fitted with an oil drain hose and tap so that the engine oil can be drained without difficulty or oil spillage.

The Control panel consists of RCBO protection, battery charge indicator, voltmeter, low oil warning lamp, emergency stop button and key start/stop switch. Socket outlet is available on request but the unit is supplied as standard with a 3m cable for connecting directly into the vehicles distribution panel. A remote key/start can also be supplied instead of the panel mounted unit.

A fuel tank is not supplied as standard as these unit are designed to operate from a remote tank, normally the vehicles existing diesel tank, again a tank can be supplied, typically a 20litre jerry can and holder which can either be attached to the generator or mounted externally.

There are two air inlet vents and one no. exhaust /hot air discharge vent.

Dimensions L 875 W 537 H 580 weight 160kg's approx
(excluding tank)

Hydraulic Power Solutions Ltd, 4 Gunnell Close, Kettering, Northants, NN15 7DJ
Tel No. 0203 286 7476 Fax No. 0845 280 2967
Email: info@hydraulicgenerators.co.uk www.shop4generators.co.uk