

SW PETROL WELDER RANGE



SW200 AC

200 AMP • HONDA GX390

- SHOWN WITH OPTIONAL TROLLEY KIT TK1101

Standard Features

- Honda four stroke engines with 'oil alert'
- Noise compliant using the latest low noise engine specification
- Dual voltage output complete with reset button overload protection
- Thermal overload protection for AC welding output
- Fully welded industrial carry frames for maximum strength
- Welder Accessory Tray

Welding Duty: 60% @ 170A

Maximum Rod Size 4.0mm

230V • 6.5kVA

115V • 2 x 2.5kVA (5.0kVA)

Standard Features

- Recoil Start Honda four stroke engines with 'oil alert'
- Noise compliant using the latest low noise engine specification
- Dual voltage output complete with reset button overload protection
- Thermal overload protection for DC welding output
- Fully welded industrial carry frames for maximum strength
- Welder Accessory Tray

Welding Duty: 60% @ 170A

Maximum Rod Size 4.0mm

230V • 4.0kVA

115V • 2.0kVA



SW200 DC

200 AMP • HONDA GX390

- SHOWN WITH OPTIONAL TROLLEY KIT TK1101

ADDITIONAL
OPTIONS

Model	Electric Start	Trolley Kit	Welding Lead Set (6M)
SW200AC		✓ TK1101	✓
SW200DC	✓	✓ TK1101	✓

STANDARD SPECIFICATIONS

Model	HP/Cyl	Start	Sockets				Fuel Tank (LT)	Run Time @75% Load	Noise		Dimensions			
			115V		230V				7M	dB Lwa	Wt	L	W	H
			16A	32A	16A	32A								
SW200AC	13/1	RC	2	-	2	-	6.5	2.6	72	97	81	690	480	540
SW200DC	13/1	RC	1	-	1	-	6.5	2.6	72	97	86	815	480	620